

Reolink-Lumus-IP-Camera-Specifications			
	Model	Reolink Lumus	
Video & Audio	Image Sensor	1/2.8" CMOS Sensor	
	Video Resolution	1920 x 1080 (2.0 Megapixels) at 15 FPS	
	Lens	f=2.8mm, F=2.0, with IR Cut	
	Video Format	H.264	
	Field of View	Horizontal: 100° Vertical: 54°	
	Day & Night	Auto-switching IR-cut filter	
	Night Vision Distance	10m (33ft) (LED: 6pcs/14mil/850nm)	
	Audio	Two-way audio	
Smart Alerts	Mode	PIR + Motion detection	
	PIR Detecting Distance	Up to 7m (21ft); Adjustable	
	PIR Detecting Angle	Horizontal: 100°	
	Alert	Instant email alerts, push notifications, siren & customized voice alerts	
Hardware Features	Power	DC 5.0V/2A, <6W	
	Spotlight	1.6W, 6500K, 180lm	
	Interface		USB 2.0
			Micro SD Card Slot (support up to 64GB micro SD card)
			Built-in Microphone and Speaker
			Reset Button
Software Features	Mainstream	Resolution: 1080p Frame rate: 2 ~ 15 FPS (default: 15 FPS) Code rate: 1024kbps ~ 2048kbps (default: 2048kbps)	
		Resolution: 704 x 480 Frame rate: 4 ~ 15 FPS (default: 10 FPS) Code rate: 128kbps ~ 768kbps (default: 384kbps)	
	Substream		
	Browser Supported	No	
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Record Mode	Motion Recording	
	Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, DHCP, DNS, DDNS, P2P	
	Maximal User Access	Support up to 4 simultaneous video streams (2 substreams & 2 mainstreams)	
WiFi	Work with	Google Assistant, Reolink Cloud * Only available in U.S., Canada, Australia, New Zealand	
	Wireless Standard	IEEE 802.11 b/g/n	
	Operating Frequency	2.4 GHz	
Working Environment	Wireless Security	WPA-PSK/WPA2-PSK	
	Temperature	Operating Temperature: -10°C ~ 55°C	
		Storage Temperature: -40°C ~ 70°C	
	Humidity	Operating Humidity: 20% ~ 85%	
		Storage Humidity: 10% ~ 90%	
Waterproof	IP65		
Size & Weight	Dimension	99 x 91 x 60mm	
	Weight	185g	
Warranty	Limited warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/	