

RLN8-410-New-Version-PoE-NVR-Specifications

Model	Model	RLN8-410 (New Version)
	Name	8-Channel 12MP PoE Network Video Recorder
	Hardware	V2
Video/Audio Input	IP Video Input	PoE IP Camera x 8
	Audio Input	Cameras with Built-In Mic
Video/Audio Output	Video Output	VGA, HDMI
	Display Resolution	HDMI: 3840*2160, 1920*1080, 1280*1024, 1280*720, 1024*768
		VGA: 1920*1080, 1280*1024, 1280*720, 1024*768
Audio Output	1-Channel, RCA	
Decoding	Video Format	H.265, H.264
	Live View/Playback Resolution	3840*2160/2560*1920/2560*1440/2048*1536/2304*1296/1080P/720P
	Synchronous Playback	1-4 Channels
Storage	SATA	1 SATA Interface (2TB HDD Included)
	External HDD	1 eSATA Interface for HDD
	Capacity	12TB (up to 6TB Capacity for Each HDD)
External Interface	USB Interface	2 x USB 2.0
	Network Interface	1, RJ-45 10/100/1000 Mbps Self-Adaptive Ethernet Interface for LAN/WAN 8, RJ-45 10/100 Mbps Self-Adaptive PoE Ethernet Interface for IP Camera
PoE	Max. Power Per Port	25W
	Supported Standard	IEEE 802.3 af/at
Network	Network Protocols	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
	Browsers Supported	Edage, Firefox, Chrome, Safari
	OS Supported	PC: Windows, Mac OS; Smart Phone: iOS, Android
	Max. User Access	20 Users
General	Power Supply	DC 48V/1.875A
	Power Consumption	<10W (Without HDD&PoE)
	Working Environment	Temperature: -10°C ~+45°C (14°F~113°F); Humidity: 10%~90%
	Dimensions	260 x 41 x 230mm
	Weight	1.2 kg (Without HDD)
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .